

LM22-L200

22" FHD LCD Monitor



Features:

- \cdot Industrial level LCD panel, suitable for extensive 24/7 continuous works
- · High fidelity digital processing, brilliant and vivid video
- · Built in stereo speakers and audio amplifier
- \cdot Suitable for every video surveillance and security application, support HDMI, VGA, BNC signal input
- \cdot Included desk stand is easily removable for standard VESA mounting
- · Support HDCVI, HDTVI, AHD and CVBS 1080P camera display













Technical Specification

Model

Model	LM22-L200
System	
Diagonal	22"(16:9)

5,555	
Diagonal	22"(16:9)
Resolution	1920×1080
Backlight	LED
Brightness/Luminance (Standard)	200cd/ m²
Contrast	1000:1
Angle of View	H170°, V160°
Response Time	5ms
Display Color	8bit(16.7M)
VESA	100×100mm

Interfaces

Input	1 HD(support HDCVI, HDTVI, 1 BNC, 1 Audio	AHD, CVBS), 1 VGA, 1 HDMI,
Output	1 HD (support HDCVI, HDTVI, AHD, CVBS), Built in speakers	
	Speaker	2W×2

General

Consumption (Standard)	≤30W
Consumption (Standby)	≤0.5W
Power Supply	AC100~240V (+/-10%), 50/60 Hz
Gross Weight	5.0kg
Dimensions(no base)	516.60x316.70x51.20mm
Work Environment	Temperature: 0°C~ 40°C
work environment	Humidity: 10%~85%

Accessory

Standard	VGA cable, power cable, pedestal
Optional	Hanging bracket

Essential Security Series | LM22-L200

Dimensions(mm)



